

Ref. No.: 722-053101410





### **Description:**

# Used HAULICK & ROOS RVD 100-910 with SCHLEICHER unwinding reel + leveler

**Build 1980** 

Specifications punching machine

- Speed ??range 50-300 min-1
- Drive power 18,5kW
- Ram stroke 10-80mm
- Ram adjustment 0-80 mm
- Peg-hole diameter. 50 mm
- Weight 15000 kg
- Of ram clamping surface 870 x 550 mm
- Working table 810 x 700 mm
- Distance between uprights 910 mm along
- Distance between table and ram at max.
  Stroke 320 mm (ram adjustment up)
- Equipment
- IMCO pressing force display device 518-2 / overload protection
- Roll feeder (+ summer Zehnder type V 132 AM)
- DC drive Baumüller GNA
- A system for roller lubricator

# H.SCHLEICHER HD 100-500 unwinding reel

**Build 1987** 

#### **Specifications**

- Maximum load 2 x 1.5 tons.
- Bandwidth 15 320mm
- Voltage 24/50 Hz 380V
- Maximum cross section 675 mm<sup>2</sup>

# H.SCHLEICHER RMS 8-53 / 160-300 leveler

**Build 1987** 

#### **Specifications**

- Drive power 11 kW
- Strip thickness 0.5 1.5mm
- Bandwidth 15 320 mm
- Straightening rollers 8 pieces

The HAULICK RVD-series is the result from tradition and innovation. Technical ones represent these precision stamping and forming presses the highest level to that today admitted stamping an forming technology. They represents precision, longevity, quality, robustness, productivity and reliability. The RVD precision stamping and forming presses offers the user, particularly with high forming strength, stamping parts of highest quality at remarkable reductions of process costs.

#### **Production features**

Generated on 17.10.2025 Page 2



- Press body in stable three-part tie rod building method provides for highest absorption characterisics and structurals rigidity
- Double connecting rod drive with eccentric shaft having 4-hold roller bearings and wide con rod distance giving high tilting rigidity of the ram also with high off-centre loads and ensure a stable BDC
- Planetary gear drive system (optional) with integrated cluth/brake combination
- Rotating mass counter balance (optional)/li>
- Integral precision ram guiding arrangement ensure that lateral forces are directly absorbed by the press frame
- Automatic stroke adjustment (optional)
- Motorised ram position adjustment, optional with quick die-lifting and fine adjustment of BDC during continuous running
- Speeds up to 400 strokes per minute

#### **Customer benefits**

Highest precision/quality, by:

- Rigid press frame made of spheroidal graphite cast iron
- High performance double connecting rod drive
- High precision ram guiding system
- High precision components are used

#### Highest economy, by:

- Long tool life time
- High flexibility for minimal tool chance time
- unbeatable reliability
- Custom-made solutions with standard components

Generated on 17.10.2025 Page 3



## Technical Data:

#### **Technical Data:**

Control: CNC

## **Dimensions and Weight:**

Weight: 9.500 kg

## **Buyer Information:**

Condition: Normal wear

Available: Sold

Sold as:

EXW (Ex Works - Incoterm)

VAT: 19 %

Location: Germany



## **Images:**



























**Asset-Trade** 

**Assessment and Sale of Used Assets world wide** 

**Am Sonnenhof 16** 

47800 Krefeld

**Germany** 

Tel.: +49 2151 32500 33