

Image not found or type unknown



Ref. No.:

923-06070853

Overview and Technical Data:

DORST - TPA 30 HS Hydraulic Powder Press

[DORST](#)



DOO

TECHN

Year of Build:
Jan 2008

Description:

Used DORST TPA30HS Hydraulic Powder Press

The press is used to produce aluminium oxide and zirconium oxide parts.

Operating 11.037 Hrs

Technical Data DORST TPA 30 HS

- Pressing force:300 kN
- Upper ram travel:180 mm
- Max. Fill height:130 mm
- Core rod travel:130 mm
- with 10mm fill height = 20 Strokes/min
- with 25 mm fill height = 10 Strokes/min

Safety:

- Safety Distance 230 mm
- Stopping Time 140 ms
- Measuring Point after U.D.C / starting point 30 mm
- Top ram Vmax 160 mm

Power:

- voltage 400 V / 50 Hz
- main drive motor 22 kW
- total power requirement 30 kW
- Dimensions of the machine ca. 3,3 x 1,6 x 3,5 m

Positioning accuracy

- Upper ram and die:0,002 mm
- Core rod:0,01 mm
- Filler drive:0,1 mm

The press is still in operation but needs a service because it presses inconsistently.

The Dorst service/repair quotation to replace all valves are 32.000 EURO, but the machine needs to be opened to see which valve(s) needs to be replacement. so the repair price will be less.

Highlights

- Short set-up times
- Precisely closed-loop controlled hold-down force
- Zero backlash guiding systems
- Programming with IPG
- Low energy consumption

Characteristics

- Die plate stationary (ejection method)
- Max. number of upper levels: 2
- Max. number of lower levels: 2
- Use of quick clamping systems
- Tool change in the machine

Technical Data:

Technical Data:

Control:

[CNC](#)

Machine Hours:

11037

Dimensions and Weight:

Height:

3.500 mm

Length:

3.300 mm

Width:

1.600 mm

Weight:

9.000 kg

Buyer Information:

Condition:

[Very good condition](#)

Available:

[Sold](#)

Sold as:

[EXW \(Ex Works - Incoterm\)](#)

VAT:

[19 %](#)

Buyers Premium:

[16 %](#)

Location:

Germany

Images:

DORST
TECHNOLOGIES

TPA 30 HS



SD 1

SD 2

Dorst Press
Ass 12079

- 1. Press change
- 2. Safety
- 3. Lubrication
- 4. Single Stroke
- 5. Cool





VERBODEN TOEGANG
De afdekplaat is niet te verwijderen
of te openen.
Alleen personeel is toegestaan.
1. Veiligheidsmaatregelen







müller
11037 h

04863425

DORST PRESS
ASS12072

DORST
TECHNOLOGIES

Typ	Baujahr	Auftrags-Nr.	Gewicht kg
TPA30HS	2008		9000

Max. Betriebsdruck [bar]
hydraulisch / pneumatisch

315/8

CE

Dorst Technologies GmbH & Co.
Kochel am See - Germany

CAUTION!

Operation of the machine without provided protective device is not permissible!

Before commissioning, study carefully and observe the operating instructions and safety instructions!

The working platform at customer's site must comply with prevailing safety regulations applicable in the user's country!

In the modes of operation tool change and setting there must be no other person except the setter in the area of danger of the machine!

Safety distance:	230	mm
Stopping time:	140	ms
Measuring point after U.D.C./ starting position:	30	mm
Top ram Vmax:	160	mm/s

ATTENTION!

Hydraulic plant resp. Pressure Accumulator Plant! Accumulator prefilled with gas under pressure. To be used with nitrogen only! Drain oil to tank before commencing any maintenance!



Asset-Trade

Assessment and Sale of Used Assets world wide

Am Sonnenhof 16

47800 Krefeld

Germany

Tel.: +49 2151 32500 33

Fax.: +49 2151 65 29 22

Email: info@asset-trade.de

Web.: <https://www.asset-trade.de/en>

Ref. No.:

923-06070853

Overview and Technical Data:

DORST - TPA 30 HS Hydraulic Powder Press

[DORST](#)



DOO

TECHN

Year of Build:
Jan 2008

Description:

Used DORST TPA30HS Hydraulic Powder Press

The press is used to produce aluminium oxide and zirconium oxide parts.

Operating 11.037 Hrs

Technical Data DORST TPA 30 HS

- Pressing force:300 kN
- Upper ram travel:180 mm
- Max. Fill height:130 mm
- Core rod travel:130 mm
- with 10mm fill height = 20 Strokes/min
- with 25 mm fill height = 10 Strokes/min

Safety:

- Safety Distance 230 mm
- Stopping Time 140 ms
- Measuring Point after U.D.C / starting point 30 mm
- Top ram Vmax 160 mm

Power:

- voltage 400 V / 50 Hz
- main drive motor 22 kW
- total power requirement 30 kW
- Dimensions of the machine ca. 3,3 x 1,6 x 3,5 m

Positioning accuracy

- Upper ram and die:0,002 mm
- Core rod:0,01 mm
- Filler drive:0,1 mm

The press is still in operation but needs a service because it presses inconsistently.

The Dorst service/repair quotation to replace all valves are 32.000 EURO, but the machine needs to be opened to see which valve(s) needs to be replacement. so the repair price will be less.

Highlights

- Short set-up times
- Precisely closed-loop controlled hold-down force
- Zero backlash guiding systems
- Programming with IPG
- Low energy consumption

Characteristics

- Die plate stationary (ejection method)
- Max. number of upper levels: 2
- Max. number of lower levels: 2
- Use of quick clamping systems
- Tool change in the machine

Technical Data:

Technical Data:

Control:

[CNC](#)

Machine Hours:

11037

Dimensions and Weight:

Height:

3.500 mm

Length:

3.300 mm

Width:

1.600 mm

Weight:

9.000 kg

Buyer Information:

Condition:

[Very good condition](#)

Available:

[Sold](#)

Sold as:

[EXW \(Ex Works - Incoterm\)](#)

VAT:

[19 %](#)

Buyers Premium:

[16 %](#)

Location:

Germany

Images:

DORST
TECHNOLOGIES

TPA 30 HS



SD 1

SD 2

Dorst Press
Ass 12079

- 1. Press change
- 2. Safety
- 3. Lubrication
- 4. Single Stroke
- 5. Full









müller
11037 h

04863425

DORST PRESS
ASS12072

DORST
TECHNOLOGIES

Typ	Baujahr	Auftrags-Nr.	Gewicht kg
TPA30HS	2008		9000

Max. Betriebsdruck [bar]
hydraulisch / pneumatisch

315/8

CE

Dorst Technologies GmbH & Co.
Kochel am See - Germany

CAUTION!

Operation of the machine without provided protective device is not permissible!

Before commissioning, study carefully and observe the operating instructions and safety instructions!

The working platform at customer's site must comply with prevailing safety regulations applicable in the user's country!

In the modes of operation tool change and setting there must be no other person except the setter in the area of danger of the machine!

Safety distance:	230	mm
Stopping time:	140	ms
Measuring point after U.D.C./ starting position:	30	mm
Top ram Vmax:	160	mm/s

ATTENTION!

Hydraulic plant resp. Pressure Accumulator Plant! Accumulator prefilled with gas under pressure. To be used with nitrogen only! Drain oil to tank before commencing any maintenance!



Asset-Trade

Assessment and Sale of Used Assets world wide

Am Sonnenhof 16

47800 Krefeld

Germany

Tel.: +49 2151 32500 33

Fax.: +49 2151 65 29 22

Email: info@asset-trade.de

Web.: <https://www.asset-trade.de/en>

Generated on 25.05.2026

© Copyright 2026 - [Asset-Trade](#)

Page