


Image not found or type unknown



Ref. No.:
945-1106949

Overview and Technical Data:

DECKEL - DMU 340P Almost New

DMG DECKEL



Year of Build:
Jan 2012

Description:

Used DMG Mori DMU 340P - 5 Axis Portal Milling centre

CNC Control Heidenhein

Low Running Hours 1024 hrs on/ 285 Spindle Hours

Clearance

- Max. X-axis travel 3.400 mm (133.9 in.)
- Max. Y-axis travel 3.400 mm (133.9 in.)
- Max. Z-axis travel 1.600 mm (63 in.)

?Table dimensions

- Max. table load 16.000 kg (35,274 lbs.)
- Table diameter 2.600 mm (102.4 in.)

Workpiece dimensions

- Max. workpiece height 1,650 mm (65 in.)

Spindle

- Standard rotational speed 10,000 rpm
- Power (100% power-on time) 32 kW (42.9 hp.)
- Torque (100% power-on time) 187 Nm (137.9 ft./lbs)

Tool magazine

- Capacity (standard) 60x

Rapid transverse

- Max. X-axis 60 m/min (196.9 ft/min)
- Max. Y-axis 30 m/min (98.4 ft/min)
- Max. Z-axis 40 m/min (131.2 ft/min)

Complete machining

- Milling and turning in one setup with the DirectDrive table with a torque up to 7,523 ft lb
- Best surface quality with technology integration grinding

Precision

- Maximum accuracy through water-cooled feed drive
- Band filter unit with 2,500 l as standard
- Highest long-term accuracy due to cooled linear guideways and active spindle growth control.

Performance

- High dynamics with feed speed up to 1,575 ipm
- Also available in mill- /turn - version
- High feed power up to 11,240 lbf
- Biggest spindle range in the market: powerMASTER motor spindle with up to 737.6 ft lb and torqueMASTER gear spindle with 1,327.6 ft lb

Efficiency

- Lower energy consumption through intelligent needs-based power units.
- Gantry design with vertically moving cross beam with hydraulic weight compensation.
- Fast innovative wheel type magazine with up to 243 tools with minimized footprint.
- Highest rigidity and dynamics up to 16.4 ft/s²

Thermosymmetrical construction

- 3-point support with an inherently stiff machine bed, no foundation required
- High temperature stability standard with positioning accuracy down to 0.38 μ in
- Position accuracy down to 0.30 μ in with accuracy pack option
- Short and continuous throat depth of milling head (no ram design)

Technical Data:

Technical Data:

Control:

[TNC 530](#)

Spindle Speed:

10.000 rpm

Tool Capacity:

60 x

Travels:

X-Axis:

3.400 mm

Y-Axis:

3.400mm

Z-Axis:

1.600 mm

Buyer Information:

Condition:

[Very good condition](#)

Availability:

[Sold](#)

Sold as:

[EXW \(Ex Works - Incoterm\)](#)

VAT:

[19 %](#)

Buyers Premium:

[16 %](#)

Location:

China

Images:











000000 h



112194 h

BAUSER

0



I



MUR

ELEKTRONI










DMU 340 P
DECKEL MAHO









Asset-Trade

Assessment and Sale of Used Assets world wide

Am Sonnenhof 16

47800 Krefeld

Germany

Tel.: +49 2151 32500 33

Fax.: +49 2151 65 29 22

Email: info@asset-trade.de

Web.: <https://www.asset-trade.de/en>

Ref. No.:
945-1106949

Overview and Technical Data:

DECKEL - DMU 340P Almost New

DMG DECKEL



Year of Build:
Jan 2012

Description:

Used DMG Mori DMU 340P - 5 Axis Portal Milling centre

CNC Control Heidenhein

Low Running Hours 1024 hrs on/ 285 Spindle Hours

Clearance

- Max. X-axis travel 3.400 mm (133.9 in.)
- Max. Y-axis travel 3.400 mm (133.9 in.)
- Max. Z-axis travel 1.600 mm (63 in.)

?Table dimensions

- Max. table load 16.000 kg (35,274 lbs.)
- Table diameter 2.600 mm (102.4 in.)

Workpiece dimensions

- Max. workpiece height 1.650 mm (65 in.)

Spindle

- Standard rotational speed 10,000 rpm

- Power (100% power-on time) 32 kW (42.9 hp.)
- Torque (100% power-on time) 187 Nm (137.9 ft./lbs)

Tool magazine

- Capacity (standard) 60x

Rapid transverse

- Max. X-axis 60 m/min (196.9 ft/min)
- Max. Y-axis 30 m/min (98.4 ft/min)
- Max. Z-axis 40 m/min (131.2 ft/min)

Complete machining

- Milling and turning in one setup with the DirectDrive table with a torque up to 7,523 ft lb
- Best surface quality with technology integration grinding

Precision

- Maximum accuracy through water-cooled feed drive
- Band filter unit with 2,500 l as standard
- Highest long-term accuracy due to cooled linear guideways and active spindle growth control.

Performance

- High dynamics with feed speed up to 1,575 ipm
- Also available in mill- /turn - version
- High feed power up to 11,240 lbf
- Biggest spindle range in the market: powerMASTER motor spindle with up to 737.6 ft lb and torqueMASTER gear spindle with 1,327.6 ft lb

Efficiency

- Lower energy consumption through intelligent needs-based power units.
- Gantry design with vertically moving cross beam with hydraulic weight compensation.
- Fast innovative wheel type magazine with up to 243 tools with minimized footprint.
- Highest rigidity and dynamics up to 16.4 ft/s²

Thermosymmetrical construction

- 3-point support with an inherently stiff machine bed, no foundation required
- High temperature stability standard with positioning accuracy down to 0.38 μ in
- Position accuracy down to 0.30 μ in with accuracy pack option
- Short and continuous throat depth of milling head (no ram design)

Technical Data:

Technical Data:

Control:

[TNC 530](#)

Spindle Speed:

10.000 rpm

Tool Capacity:
60 x

Travels:

X-Axis:
3.400 mm
Y-Axis:
3.400mm
Z-Axis:
1.600 mm

Buyer Information:

Condition:
Very good condition
Availability:
Sold
Sold as:
EXW (Ex Works - Incoterm)
VAT:
19 %
Buyers Premium:
16 %
Location:
China

Images:











000000 h



112194 h

BAUSER

0



I




MUR

ELEKTRONI












DMU 340 P
DECKEL MAHO



Two people are visible on the upper level, looking down at the machine.









Asset-Trade

Assessment and Sale of Used Assets world wide

Am Sonnenhof 16

47800 Krefeld

Germany

Tel.: +49 2151 32500 33

Fax.: +49 2151 65 29 22

Email: info@asset-trade.de

Web.: <https://www.asset-trade.de/en>

Generated on 18.02.2026

© Copyright 2026 - [Asset-Trade](#)

Page